



CCL-72-J2888

Item Number 9884730

Charging hose set 1/4", for automotive applications

- Tested according to SAE J2196 and J2888
- Long-life PTFE seal with blow-out preventer, replaceable
- 60 bar working pressure
- High-quality rubber compound for high elasticity, against hardening and embrittlement
- Fixing nut serrated for better hand tightening, and with 14mm hexagon

Technical Data

Material	Brass Rubber
Colour	yellow blue red
Number of Hoses	3
Length	180 cm
Sealing	PTFE
System Connection	1/4" SAE bend 45°
Device Connection	1/4" SAE
Valve Core Depressor	Yes
Ball Valve	No
Working Pressure	60 bar
Burst Pressure	300 bar
Standards	
Diameter	1/4"
Packaging	Blister

Accessories

4661147 CA-1/2"-20UNF-Y	Ball valve, yellow, 1/2"-20UNF X 1/2"-20UNF
4661121 CA-1/2"-20UNF-B	Ball valve, blue, 1/2"-20UNF X 1/2"-20UNF
4661139 CA-1/2"-20UNF-R	Ball valve, red, 1/2"-20UNF X 1/2"-20UNF
4682446 CA-1/2"-20UNF-Y-45°	Ball valve for charging hose, yellow with threaded hull 45° bent
4682420 CA-1/2"-20UNF-B-45°	Ball valve, blue with threaded hull 45° bent
4682438 CA-1/2"-20UNF-R-45°	Ball valve for charging hose, red with threaded hull 45° bent

Spare Parts

9880871 P-509-T/10	PTFE gasket 1/4" SAE, 10 pieces
9883979 P-509-T/100	PTFE gaskets, 100 pieces

Acknowledged globally



9880869 P-513/10 Core depressor 1/4", 10 pieces
9883961 P-513/100 Core depressor 1/4", 100 pieces